







MULTI-RANGE DIGITAL TIMER 多段式數位型限時繼電器

SPECIFICATION 規格		AH2D-NDM	AH2D-YDM
Model 型號			
Dimension(mm) 尺寸		61H*49W*70D	88H*58W*68D
Time Range 時間範圍		x.01Sec, x0.1Sec, x1Sec, x.59Sec x0.1Min, x1Min, x.59Min x0.1Hr, x1Hr, x10Hr	
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz	
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載	
Reset Time 複歸時間		0.1 sec max	
Consumed Power 消耗功率		3VA	
Ambient Temperature 使用周圍溫度		-10°C ~ +55°C	
Ambient Humidity 使用周圍濕度		45~85%RH	
Life 壽命	Mechanical 機械	5×10 ⁶ times	
	Electrical 電氣	10 ⁵ times	
Weight 重量		160g	
Connection 接線圖		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>限時2C</p>  <p>mode A</p> </div> <div style="text-align: center;"> <p>限時1C, 瞬時1C</p>  <p>mode B</p> </div> </div>	
Timing Chart 時序圖		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>Rt: Resetting time</p> </div> <div style="text-align: center;">  <p>Rt: Resetting time</p> </div> </div>	